

**MUSTER 4.5KG**

JSG Industrial is proud to offer 2 types of 4.5kg extinguisher to suit a wider range of applications.

**Comparing the 2 options;**

Firstly we offer the Standard 4.5kg extinguisher model. A quality unit giving you a fire extinguisher when you need it at a cost effective price. Rated at 4A:60BE.

Secondly we have the Hi-Performance 4.5kg extinguisher model. With the introduction of new powder, a thicker walled cylinder, a new heavy duty valve and handle with double rivets JSG offers a class leading product which is capable of extinguishing the most fierce of fires with greater efficiency. Ideally suited in circumstances where a faster and safer 'knock down' is required such as mine sites, service stations and any high risk area due to its improved rating of 4A:80BE.

	STANDARD 4.5KG	HI-PERFORMANCE 4.5KG
Part Number	43-G4.5ABE	43-G4.5ABEH
Agent Capacity	4.5kg	4.5kg
Agent Type	ABE Dry Chemical Powder	ABE Dry Chemical Powder
Total Mass	7.8kg	7.9kg
Fire Rating	4A:60B:E	4A:80B:E
Approvals	AS/NZS 1841.5	AS/NZS 1841.5
Nozzle Size	4.4mm	4.0mm
Pressure	1400 kPa	1400 kPa
Discharge Time	19 seconds	22 seconds
Dimensions (w) x (h)	145mm x 560mm	145mm x 500mm
Cylinder Pressure Test	5 Yearly	5 Yearly
Periodic Test Pressure	2.5 MPa	2.5 MPa
Cylinder Construction	Steel	Steel
Valve Construction	Brass	Brass
Cylinder Finish	Powder Coated Red	Powder Coated Red
Handle Finish	Stainless Steel	Stainless Steel
Valve Finish	Nickel Plated Brass	Nickel Plated Brass



43-G4.5ABE



43-G4.5ABEH



COMES WITH WALL BRACKET

**MUSTER 9KG**

JSG Industrial is proud to offer 2 types of 9kg extinguisher to suit a wider range of applications.

**Comparing the 2 options;**

Firstly we offer the Standard 9kg extinguisher model. A quality unit giving you a fire extinguisher when you need it at a cost effective price. Performance rating of 6A:80BE.

Secondly we have the Hi-Performance 9kg extinguisher model. With the introduction of a thicker walled cylinder, a new heavy duty valve head with double rivets JSG Industrial has created a class leading product which is not only capable of extinguishing ferocious fires but will also withstand daily abuse in the most harsh environments. The High Performance 9.0kg is ideal for situations such as mining sites and vehicles where frequent knocks, scrapes and abuse is a serious consideration. In these rugged locations our high performance 9.0kg extinguisher excels. Performance rating of 6A:80BE.

	STANDARD 9KG	HI-PERFORMANCE 9KG
Part Number	43-9ABE	43-9ABEH
Agent Capacity	9.0kg	9.0kg
Agent Type	ABE Dry Chemical Powder	ABE Dry Chemical Powder
Total Mass	13.9kg	14.2kg
Fire Rating	6A:80B:E	6A:80B:E
Approvals	AS/NZS 1841.5	AS/NZS 1841.5
Nozzle Size	6.0mm	6.0mm
Pressure	1400 kPa	1400 kPa
Discharge Time	22 seconds	22 seconds
Dimensions (w) x (h)	183mm x 615mm	183mm x 555mm
Cylinder Pressure Test	5 Yearly	5 Yearly
Periodic Test Pressure	2.5 MPa	2.5 MPa
Cylinder Construction	Steel	Steel
Valve Construction	Brass	Brass
Cylinder Finish	Powder Coated Red	Powder Coated Red
Handle Finish	Stainless Steel	Stainless Steel
Valve Finish	Nickel Plated Brass	Nickel Plated Brass



43-9ABE



43-9ABEH



COMES WITH WALL BRACKET